

MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards



HMIS HAZARD RATINGS

HEALTH	0	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME
REACTIVITY	0	2 = MODERATE	

TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:	Not Regulated		
HAZARD CLASS / PKG GRP:	None / None	REF:	Not Applicable
IDENTIFICATION NUMBER:	None	LABEL:	None Required

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

ASTEC CAULK #2001

Page 1 of 2

MANUFACTURER'S NAME Insulating Coatings Corporation	EMERGENCY TELEPHONE NUMBER CHEM • TEL (800) 255-3924 Outside USA (813) 248-0573
ADDRESS (NUMBER, STREET, P.O. BOX) 956 South Hwy 41	TELEPHONE NUMBER FOR INFORMATION (800) 345-5306
(CITY, STATE AND ZIP CODE) Inverness, FL 34450-	DATE PREPARED: November 18, 2000 SUPERSEDES: March 26, 1993

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS <small>(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))</small>	CAS #	% <small>(OPTIONAL)</small>	OSHA PEL		ACGIH TWA		SARA	RQ
			PPM	MG/M ³	PPM	MG/M ³	TITLE III	LBS

No hazardous materials present as defined in 29 CFR 1910.1000, 40 CFR 260 - 281, 302, 355, 370, 372 or WHMIS.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: None expected, however, certain individuals may be sensitized and experience minor nausea or headaches.	INHALATION: Remove affected person to fresh air; if symptoms persist seek medical attention.
SKIN: None expected, however, prolonged contact may cause irritation.	SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.
EYES: Contact with eyes may cause irritation.	EYES: Remove contact lenses. Flush eyes with water for 15 minutes; if irritation persists, seek medical attention.
INGESTION: May cause gastric distress, vomiting and diarrhea.	INGESTION: Give two glasses of water for dilution; DO NOT induce vomiting seek medical attention.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; no known chronic effects have been established.

CARCINOGENICITY NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)
 ASTEC CAULK # 2001

Page 2 of 2
 Date: November 18, 2000

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED) Non-flammable	NFPA RATING None	FLAMMABLE LIMITS LEL: Not applicable UEL: Not applicable
--	---------------------	---

EXTINGUISHING MEDIA
 Carbon dioxide, water, water fog, dry chemical, chemical foam

SPECIAL FIRE FIGHTING PROCEDURES
 Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.

UNUSUAL FIRE AND EXPLOSION HAZARDS
 None

SECTION 5 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills - wash to sanitary sewer with plenty of water. Large spills - soak up with approved absorbent, shovel product into approved container for disposal. Wash area with plenty of water.

SECTION 6 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): None required.

VENTILATION LOCAL EXHAUST: Not necessary MECHANICAL (GENERAL): Recommended	SPECIAL: None OTHER: None
PROTECTIVE GLOVES: Recommended for general protection	EYE PROTECTION: Recommended for general protection
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby	

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT Not applicable	SPECIFIC GRAVITY (WATER = 1) 1.620
VAPOR PRESSURE (MM Hg) Not applicable	VOLATILE ORGANIC COMPOUNDS (VOC's) None
VAPOR DENSITY (AIR = 1) Not applicable	EVAPORATION RATE (WATER = 1) Not applicable
SOLUBILITY IN WATER Not determined	% VOLATILE (BY WEIGHT) < 30%
APPEARANCE AND ODOR Smooth paste, slight characteristic odor	pH Not determined

SECTION 9 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Extreme temperatures
---------------------------------------	--

INCOMPATIBILITY (MATERIALS TO AVOID):
 Strong oxidizers, strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None
---	------------------------------

SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Products classified as non - hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.