

MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards

HMIS HAZARD RATINGS



HEALTH	1	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME
REACTIVITY	0	2 = MODERATE	

TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:	Not Regulated		
HAZARD CLASS / PKG GRP:	None / None	REF:	Not Applicable
IDENTIFICATION NUMBER:	None	LABEL:	None Required

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

Page 1 of 2

ASTEC 2000 Fibered Finish Coat

MANUFACTURER'S NAME Insulating Coatings Corporation	EMERGENCY TELEPHONE NUMBER CHEM • TEL (800) 255-3924 Outside USA (813) 248-0573
ADDRESS (NUMBER, STREET, P.O. BOX) 956 South Hwy 41	TELEPHONE NUMBER FOR INFORMATION (800) 345-5306
(CITY, STATE AND ZIP CODE) Inverness, FL 34450-	DATE PREPARED: November 12, 2003 SUPERSEDES: New

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (OPTIONAL)	OSHA PEL		ACGIH TWA		SARA TITLE III	RQ LBS
			PPM	MG/M3	PPM	MG/M3		
Butyl benzyl phthalate (a,b,c)	85-68-7	1 - 5		*5		*5	Yes	100
Ethylene glycol monopropyl ether (a)	2807-30-9	1 - 5	not established				Yes	

- (a) A "YES" in the SARA TITLE III column in Section 2 indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.
- (b) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture = 4000 lbs) or greater amounts, according to 40 CFR 302.
- (c) Product is listed or defined as a marine pollutant in IMDG Code or 49 CFR 172.101 Appendix B, List of Marine Pollutants and must be classified as an Environmentally Hazardous Substance, Class 9, in addition to any other defined hazards for this product.
- (*) The ACGIH Time Weighted Average (TWA) has not been established nor has OSHA established the Permissible Exposure Limit (PEL) for this product, therefore the limits described have been established as guidelines by the manufacturer.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.	INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.
SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis.	SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.
EYES: Contact causes severe irritation and pain associated with redness and swelling of the conjunctiva.	EYES: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
INGESTION: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis.	INGESTION: Give two glasses of water for dilution; Induce vomiting by sticking fingers down throat; never give anything by mouth to an unconscious person; seek medical attention.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; no known chronic effects have been established.

CARCINOGENICITY NTP? No IARC MONOGRAPHS? No OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET		
IDENTITY (AS USED ON LABEL AND LIST) ASTEC 2000 Fibered Finish Coat		Page 2 of 2 Date: November 12, 2003
SECTION 4 - FIRE FIGHTING MEASURES		
FLASH POINT (METHOD USED) Non-flammable	NFPA RATING None	FLAMMABLE LIMITS LEL: Not applicable UEL: Not applicable
EXTINGUISHING MEDIA Carbon dioxide, water, water fog, dry chemical, chemical foam		
SPECIAL FIRE FIGHTING PROCEDURES Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.		
UNUSUAL FIRE AND EXPLOSION HAZARDS None		
SECTION 5 - ACCIDENTAL RELEASE MEASURES		
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills - wash to sanitary sewer with plenty of water. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to SARA Title III, Section 313 40 CFR 372, and CERCLA 40 CFR 302 for complete regulations concerning reporting requirements.		
SECTION 6 - HANDLING AND STORAGE		
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.		
SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION		
RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.		
VENTILATION LOCAL EXHAUST: Required MECHANICAL (GENERAL): Yes	SPECIAL: To maintain minimum TWA and STEL levels. OTHER: Engineering and work controls as required.	
PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs.	EYE PROTECTION: Goggles with side shields; safety eyebath nearby.	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls, apron, or other equipment should be worn to minimize skin contact.		
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.		
SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES		
BOILING POINT 212° F	SPECIFIC GRAVITY (WATER = 1) 1.485	
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C	VOLATILE ORGANIC COMPOUNDS (VOC's) 0.506 lbs / gallon (calculated on water-free basis)	
VAPOR DENSITY (AIR = 1) < 1	EVAPORATION RATE (n-Butyl Acetate = 1) < 1	
SOLUBILITY IN WATER Dispersible	% VOLATILE (BY WEIGHT) 27%	
APPEARANCE AND ODOR White viscous liquid, characteristic odor	pH 7.5 - 8.5	
SECTION 9 - STABILITY AND REACTIVITY		
STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Extreme temperatures	
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids		
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.		
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None	
SECTION 10 - DISPOSAL CONSIDERATIONS		
WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Products classified as non - hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.		
The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.		