

# MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards



## HMIS HAZARD RATINGS

HEALTH	1	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME
REACTIVITY	0	2 = MODERATE	

## TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:	Not Regulated		
HAZARD CLASS / PKG GRP:	None / None	REF:	Not Applicable
IDENTIFICATION NUMBER:	None	LABEL:	None Required

## SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

**ASTEC WPM # 9**

Page 1 of 2

MANUFACTURER'S NAME

Insulating Coatings Corporation

EMERGENCY TELEPHONE NUMBER

CHEM • TEL (800) 255-3924 Outside USA (813) 248-0573

ADDRESS (NUMBER, STREET, P.O. BOX)

956 South Hwy 41

TELEPHONE NUMBER FOR INFORMATION

(800) 345-5306

(CITY, STATE AND ZIP CODE)

Inverness, FL 34450-

DATE PREPARED: November 18, 2000

SUPERSEDES: April 22, 1993

## SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (OPTIONAL)	OSHA PEL		ACGIH TWA		SARA TITLE III	RQ LBS
			PPM	MG/M <sup>3</sup>	PPM	MG/M <sup>3</sup>		
Ethylene glycol (a,b,c)	107-21-1	1 - 5	50 C		100 C		Yes	5000
Zinc oxide (as zinc) (a)	1314-13-2	1 - 5	15		10		Yes	

(a) A "YES" in the SARA TITLE III column in Section 2 indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

(b) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24,000 lbs) or greater amounts, according to 40 CFR 302.

(c) A "C" in the OSHA PEL or ACGIH TWA column indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.

## SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: None expected, however, certain individuals may be sensitized and experience minor nausea or headaches.

INHALATION: Remove affected person to fresh air; if symptoms persist seek medical attention.

SKIN: None expected, however, prolonged contact may cause irritation.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: This product is an eye irritant. Contact with the eyes will cause irritation.

EYES: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: May cause gastric distress, vomiting and diarrhea.

INGESTION: Give two glasses of water for dilution; DO NOT induce vomiting; seek medical attention; never give anything by mouth to an unconscious person.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; no known chronic effects have been established.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

**MATERIAL SAFETY DATA SHEET**

IDENTITY (AS USED ON LABEL AND LIST)

ASTE C WPM # 9

Page 2 of 2

Date: November 18, 2000

**SECTION 4 - FIRE FIGHTING MEASURES**

FLASH POINT (METHOD USED)

Non-flammable

NFPA RATING

None

FLAMMABLE LIMITS

LEL: Not applicable

UEL: Not applicable

EXTINGUISHING MEDIA

Carbon dioxide, water, water fog, dry chemical, chemical foam

SPECIAL FIRE FIGHTING PROCEDURES

Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None

**SECTION 5 - ACCIDENTAL RELEASE MEASURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills - wash to sanitary sewer with plenty of water. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to SARA Title III, Section 313 40 CFR 372, and CERCLA 40 CFR 302 for complete regulations concerning reporting requirements.

**SECTION 6 - HANDLING AND STORAGE**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

**SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

RESPIRATORY PROTECTION (SPECIFY TYPE): None required; however, if misting occurs, NIOSH approved respirator capable of removing particulate from air must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

VENTILATION

LOCAL EXHAUST: Not necessary

SPECIAL: None

MECHANICAL (GENERAL): Recommended

OTHER: None

PROTECTIVE GLOVES: Recommended for general protection

EYE PROTECTION: Safety goggles with side shields

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

**SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES**

BOILING POINT

212° F

SPECIFIC GRAVITY (WATER = 1)

1.220

VAPOR PRESSURE (MM Hg)

17 mm Hg @ 20 ° C

VOLATILE ORGANIC COMPOUNDS (VOC's)

0.1 lbs / gallon

VAPOR DENSITY (AIR = 1)

&lt; 1

EVAPORATION RATE (n-Butyl Acetate = 1)

&lt; 1

SOLUBILITY IN WATER

Partially soluble

% VOLATILE (BY WEIGHT)

30%

APPEARANCE AND ODOR

White viscous liquid, slight characteristic acrylic odor

pH

9.0 - 9.8

**SECTION 9 - STABILITY AND REACTIVITY**

STABILITY

UNSTABLE:

STABLE: XXX

CONDITIONS TO AVOID:

Extreme temperatures

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong oxidizers, strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

HAZARDOUS POLYMERIZATION

MAY OCCUR:

WILL NOT OCCUR: XXX

CONDITIONS TO AVOID:

None

**SECTION 10 - DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Products classified as non - hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.